

PRODUCT-DETAILS

168FLR3-B0240

HOUSING FOR 8.3KV CLF



General Information

Extended Product Type	168FLR3-B0240
Product ID	7TAA124110R0043
EAN	0783786513857
Catalog Description	HOUSING FOR 8.3KV CLF
Long Description	Molded Current Limiting Fuse Housing, Nominal Fuse Voltage Rating 8.3kV, Fuse Test Port - Two Capacitive Test Ports, Large Housing, Cable Insulation Diameter 0.635 inch - 0.905 inch / 16-23mm, Aluminum Conductor size 1/0 AWG Stranded/Compressed, 2/0 AWG Solid/Compact.

Ordering

EAN	0783786513857
Customs Tariff Number	8535908020

Dimensions

Product Net Weight	9.27 lb 4.204 kg
--------------------	---------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Protect Light Duty Underground Distribution Systems
Brand / Label	Elastimold
Color	Black
Current Rating	200 A
Insulation Material	Yes, EPDM Rubber
Material	EPDM Rubber
Number of Batteries	0
Product Name	ELECTRICAL CONNECTOR,>1000V
Product Type	Loadbreak Fused Elbow Connector
Size	Length 21.12 inches from bottom to center of Bushing
Special Functions	Full-Range Current-Limiting Fusing with 50kA Interrupting Capability. Hotstick Operable 15kV Loadbreak Elbow Switching.
Standards	IEEE 386, ANSI C37.40, ANSI C37.41, ANSI C37.47
Temperature Range	-40 to +65 °C
UPC	783786513857
Voltage Rating	8.3 kV

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	168FLR3-B0240
Instructions and Manuals	168FLR3-B0240

Classifications

UNSPSC	39121421
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4586 >> Electrical connector assembly

Categories

Low Voltage Products and Systems → Installation Products → Cable Accessories and Apparatus → Cable Accessories

